




短节距精密滚子链链轮

Short pitch precision roller chain wheels


3/8" * 7/32" 06B-1-2-3 GB1244-1997 DIN8187 ISO/R606	链轮齿部参数MM		
		节距 P 滚子直径 d-φ 元弧半径 r3 倒角宽度 C 齿宽 B1 齿宽 b1 齿宽 B2 齿宽 B3	9.525 6.35 10 1 5.3 5.2 15.4 25.6



A型单排平片链轮
A type simplex plate wheels



A型双排平片链轮
A type duplex plate wheels



A型叁排平片链轮
A type triplex plate wheels

齿数 Z	外径 de	节径 dp	单排链轮 Simplex			双排链轮 Duplex			叁排链轮 Triplex		
			dm	D1	A	dm	D2	A	dm	D3	A
8	28.6	24.89	15	8	20	15	8	25	15	8	32
9	31.5	27.85	18	8	20	18	8	25	18	8	32
10	34.5	30.82	20	8	20	20	8	25	20	8	32
11	37.5	33.8	22	8	25	22	10	30	22	10	35
12	40.5	36.8	25	8	25	25	10	30	25	12	35
13	43.5	39.8	28	8	25	28	10	30	28	12	35
14	46.5	42.8	31	8	25	31	10	30	31	12	35
15	49.5	45.81	34	8	25	34	10	30	34	12	35
16	52.5	48.82	37	10	28	37	12	30	37	12	35
17	55.5	51.83	40	10	28	40	12	30	40	12	35
18	58.6	54.85	43	10	28	43	12	30	43	12	35
19	61.6	57.87	45	10	28	46	12	30	46	12	35
20	64.6	60.89	46	10	28	49	12	30	49	12	35
21	67.6	63.91	48	12	28	52	16	30	52	16	40
22	70.6	66.93	50	12	28	55	16	30	55	16	40
23	73.7	69.95	52	12	28	58	16	30	58	16	40
24	76.7	72.97	54	12	28	61	16	30	61	16	40
25	79.7	76	57	12	28	64	16	30	64	16	40
26	82.7	79.02	60	12	28	67	16	30	67	16	40
27	85.7	82.04	60	12	28	70	16	30	70	16	40
28	88.8	85.07	60	12	28	73	16	30	73	16	40
29	91.8	88.09	60	12	28	76	16	30	76	16	40
30	94.8	91.12	60	12	28	79	16	30	79	16	40
31	97.9	94.14	65	14	30	80	16	30	80	16	40
32	100.9	97.17	65	14	30	80	16	30	80	16	40
33	103.9	100.2	65	14	30	80	16	30	80	16	40
34	106.9	103.23	65	14	30	80	16	30	85	16	40
35	110	106.26	65	14	30	80	16	30	85	16	40
36	113	109.29	70	16	30	90	16	30	90	16	40
37	116	112.32	70	16	30	90	16	30	90	16	40
38	119	115.34	70	16	30	90	16	30	90	16	40
39	122.1	118.37	70	16	30	90	16	30	90	16	40
40	125.1	121.4	70	16	30	90	16	30	90	16	40
50	156.3	151.69	80	20	30	90	20	30	90	20	40
60	186.6	181.99	80	20	30	90	20	30	90	20	40

