



短节距精密滚子链链轮

Short pitch precision roller chain wheels

2"×1 1/4
32B-1-2-3
GB1244-1997
DIN8187
ISO/R606




链轮齿部参数MM		
节距	P	50.8
滚子直径	d-φ	29.21
元弧半径	r3	51
倒角宽度	C	6
齿宽	B1	29.4
齿宽	b1	28.8
齿宽	B2	87.7
齿宽	B3	146




A型单排平片链轮

A type simplex plate wheels



A型双排平片链轮

A type duplex plate wheels



A型叁排平片链轮

A type triplex plate wheels

齿数 Z	外径 de	节径 dp	单排链轮			双排链轮			叁排链轮		
			Simplex			Duplex			Triplex		
			dm	D1	A	dm	D2	A	dm	D3	A
8	153.2	132.69	82	25	80	82	30	120	82	30	180
9	159	148.54	88	25	80	88	30	120	88	30	180
10	185	164.54	104	25	80	104	30	120	104	30	180
11	200.8	180.34	120	30	80	120	30	120	120	30	180
12	216.8	196.29	133	30	80	133	30	120	133	30	180
13	232.8	212.29	145	30	80	145	30	120	145	30	180
14	248.8	228.29	145	30	80	145	30	120	145	30	180
15	264.8	244.3	145	30	80	160	30	120	160	30	180
16	280.9	260.4	160	30	90	180	30	120	160	30	180
17	296.9	276.4	160	30	90	180	30	120	180	30	180
18	313	292.55	160	30	90	200	30	120	180	30	180
19	329.1	308.66	160	30	90	200	30	120	200	30	180
20	345.2	324.71	180	30	90	200	30	120	200	30	180
21	361.3	340.82	180	30	90	200	30	120	200	40	180
22	377.5	356.98	180	30	90	200	30	120	200	40	180
23	393.6	373.08	180	30	90	200	30	120	200	40	180
24	409.7	389.18	180	30	90	200	30	120	200	40	180
25	425.8	405.33	180	30	90	200	30	120	200	40	180
26	441.9	421.44	180	30	90	200	30	120	200	40	180
27	458.1	437.59	180	30	90	200	30	120	200	40	180
28	474.2	453.69	180	30	90	200	30	120	200	40	180
29	490.4	469.9	180	30	90	200	30	120	200	40	180
30	506.5	486	180	30	90	200	30	120	200	40	180
32	538.8	518.26	180	30	90	200	30	120	200	40	180
35	589.5	566.72	180	30	90	200	30	120	200	40	180
38	635.5	615.14	180	30	90	200	30	120	200	40	180
40	670.3	647.49	180	30	90	200	30	120	200	40	180
45	751	728.25	180	30	100	200	30	120	200	40	180
50	831.8	809.04	180	30	100	200	30	120	200	40	180

